Oktober 2022



Guidance

Training Matrix

For selection of the appropiate training by users

For selection of the right training, apply the principle «process of elimination».

Start to check of the respective task of your

employee is covered by Advanced Training (Level 3), if not, check if Intermediate Training (Level 2) applies, if not \rightarrow the general training (Level 1) is sufficient.





| Level | Definition | Content as defined in the <u>legislation</u> | Training Platform | Coverage |
|-------|---------------------|--|----------------------|--|
| | General Training | | T 045 | General training containing all aspea which are defined in the legal text |
| | | | T 048 | These are all general trainings , contain |
| | | | T 049 | all aspects which are defined in the le text, but with a specific focus on th adhesives and sealants sector. |
| | | | T 050 | |
| | | | T 051 | |
| | | | | |



| Level | Definition | Content as defined in the <u>legislation</u> | Training Platform | Coverage |
|-------|--------------|--|----------------------|---|
| 2 | Intermediate | Handling open mixtures at ambient temperature (incl foam tunnels) Spraying in a ventilated booth Application by roller Application by brush Application by dipping and pouring Mechanical post treatment (e.g., cutting) of not fully cured articles which are not warm anymore Cleaning and waste Any other uses with similar exposure through the dermal and/or inhalation route Additional behavior-based aspects Maintenance Management of change Evaluation of existing safety instructions Risk in relation to application process used | T 007 | Dipping or pouring , open mixture, cleaning waste |
| | | | T 015 | Handling of open mixtures at ambient temperatures , cleaning and waste |
| | | | T 020 | Application by brush or roller, open handlin hot and warm formulations, cleaning and v |
| | | | T 022 | Application by brush or roller, cleaning a waste |
| | | | T 042 | Cleaning and Waste |
| | | | T 052 | Industrial application of polyurethane adhe at ambient temperatures without sprayin Adhesives and sealants for industrial bondir ambient temperatures without spraying |
| | | | T 070 | Production & Formulation of Diisocyanate containing Products |
| | | | T 071 | Continuous Manufacturing of Elastomers (i TPU) Training Program |
| | | | T 072 | Appliances Production Training Program |



| Level | Definition | Content as defined in the <u>legislation</u> | Training Platform | Coverage |
|-------|----------------------|---|----------------------|--|
| 3 | Advanced Training | Handling incompletely cured articles (e.g., freshly cured, still warm) Foundry applications Maintenance and repair that needs access to equipment | T 003 | Spraying in a ventilated booth , open mixtures cleaning and waste |
| | | | T 005 | Application by brush or roller, open mixture, clear and waste |
| | | | T 011 | Spraying outside a ventilated booth, open mixtur cleaning and waste |
| | | | T 012 | Foundry Industry |
| | | Open handling of warm or hot formulations (> 45 °C) | T 013 | Other (non-spraying) application process of Paints Coatings, open handling of hot or warm formulati |
| | | | T 018 | Spraying in a ventilated booth, cleaning and was |
| | | Spraying in open air, with limited or only natural ventilation (includes large industry working halls) and spraying with high energy (e.g., foams, elastomers) And any other uses with similar exposure through the dermal and/or inhalation route | T 019* | Professional Uses – Spray Booth Application |
| | | | T 023* | Professional painting with brush or roller |
| | | | T 024 | Application by dipping or pouring, open handling of or warm chemical formulations (≥ 40°C), cleaning waste |
| | | | T 033 | Spraying outside a ventilated booth , Open handlin hot or warm formulation, Cleaning and waste |
| | | | T 034* | Professional Uses – Spraying Outside Application |
| *The | | | T 035 | Spraying outside a ventilated cabin, cleaning ar waste |
| | | | T 037 | Maintenance and repair with possible diisocyand contact, handling of hot or warm chemical formula (≥ 40°C). Cleaning and waste |
| | | | T 039 | Open handling of hot or warm formulations (>45° cleaning and waste |
| | | | T 040 | Maintenance and repair with possible diisocyand contact, cleaning and waste |



| Level | Definition | Content as defined in the <u>legislation</u> | Training Platform | Coverage |
|-------|----------------------|--|----------------------|---|
| 3 | Advanced Training | Handling incompletely cured articles (e.g., freshly cured, still warm) | T 046 | Flexible moulded foam |
| | | | T 047 | Flexible Slabstock Foam |
| | | Foundry applications Maintenance and repair that needs access to | T 053 | Industrial application of polyurethane adhesives, process steps above 45 °C or by spraying or at laminating speeds above 100 m/min |
| | | equipment Open handling of warm or hot formulations (> 45 °C) | T 054 | Industrial application of polyurethane adhes - Maintenance and repair of equipment |
| | | | T 055 | Risk Management Measures for MDI in factor produced rigid PU foam |
| | | Spraying in open air, with limited or only natural ventilation (includes large industry working halls) and spraying with high energy (e.g., foams, elastomers) | T 056 | Print Shops – 2 Component Inks |
| | | | T 057 | Wood composites products |
| | | And any other uses with similar exposure through the dermal and/or inhalation route | | |



CONTACTS:

Jörg Palmersheim Secretary General

Kristine Dewaele

Office Manager

Brieuc Lits

Communication Manager

joerg.palmersheim@isopa.org www.isopa.org www.alipa.org www.polyurethanes.org

6 | September 2022